









<b>A1</b> m kg		1.00 11850*	2.50 4730**	4.34 2730	6.14 1910								
<b>A2</b> m kg		1.00 11270*	2.50 4470**	4.42 2550	6.23 1800	8.10 1360	10.16 1000	12.23 730	14.42 545				
<b>A3</b> m kg		1.00 10960*	2.50 4330**	4.51 2430	6.31 1700	8.18 1260	10.16 1000	12.23 730	14.42 545	16.54 300			
<b>A4</b> m kg		1.00 10670*	2.50 4210**	4.60 2320	6.40 1580	8.27 1160	10.25 890	12.23 730	14.42 545	16.54 300			
<b>A5</b> m kg		1.00 10530*	2.50 4150**	4.68 2250	6.48 1535	8.35 1110	10.33 835	12.31 665	14.31 545	16.54 300			
<b>A3J2</b> m kg										12.85 450	14.22 395	15.70 350	17.30 280

\*) Theoretical lifting capacity  
 \*\*) Capacity at fixed hook (only if with load limiting device in EC area)

MODELS	LIFTING MOMENT	SLEWING ANGLE	WORKING PRESSURE	OIL TANK CAPACITY	MAX OIL FLOW	MAX. VERTICAL REACH (HYDR.)	CRANE WEIGHT (STAB. STANDARD)	DIMENSIONS
	tm	°	bar	l	l/min	m	kg	mm BxhxS
<b>A1</b>	11,9	380	310	100	25	9,6	1545	2460x2340x855
<b>A2</b>	-	380	310	100	25	11,5	1665	2460x2340x855
<b>A3</b>	-	380	310	100	25	13,5	1770	2460x2340x855
<b>A4</b>	-	380	310	100	25	15,5	1865	2485x2340x855
<b>A5</b>	-	380	310	100	25	17,6	1955	2500x2340x940
<b>A3J2</b>	-	380	290	100	25	18,8	2080	2490x2340x1030